## PATENT ABSTRACTS OF JAPAN

(11)Publication number:

06-140898

(43)Date of publication of application: 20.05.1994

(51)Int.CI.

H03K 17/687

(21)Application number: 04-126999

(71)Applicant:

**NEC CORP** 

(22)Date of filing:

20.05.1992

(72)Inventor:


AMAUCHI MASAKAZU

## (54) GATE BOOSTING CIRCUIT OF TRANSFER GATE TRANSISTOR

(57)Abstract:

PURPOSE: To prevent gate oxide film distruction by means of a gate excess voltage which is impressed to a transfer gate node and is charged-up.

CONSTITUTION: A gate selecting and voltage protecting circuit 14 which inputs a transfer gate selecting signal SEL with a power source voltage VD and grounded point potential GND as 'H' and 'L' levels and for which a gate node voltage S2 (the sum of the power source voltage VD and an analog input voltage vi) outputted from a charge-up circuit 15 is supplied is provided. The voltage protecting circuit 14 applies the analog input voltage vi to the node N3 as the charged-up input voltage S3 through a second transfer gate transistor 13. Then, in the charge-up circuit 15, the power srouce voltage VD is added by a capacitance element C, charge-up is executed and the gate node voltage S2 is supplied to the transfer gate node N2. Therefore, the gate node voltage S2 is just higher than the analog input voltage vi only by power source voltage VD so that gate excess voltage distruction is prevented.



## **LEGAL STATUS**

[Date of request for examination]

25.04.1996

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

2803463

[Date of registration]

17.07,1998

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right]

Copyright (C); 1998,2003 Japan Patent Office